Mactronic®

TRUSTED BY PROS®

ULTIMO X1000

ANSI FL1 STANDARD | 1000 lm | 170 m

PHL0012

APPLICATIONS: INDUSTRIAL, WORKSHOP & DIY, CONSTRUCTION

POWER SUPPLY	Li-Ion 3,7V 5200 mAh (2 x 18650 Li-Ion 3,7V 2600 mAh)		
CHARGING TIME	4 h 30 min		
	LIGHT OUTPUT	**RUN TIME**	**BEAM DISTANCE**
ADS	12 lm - 1000 lm	3 h 30 min - 148 h	20 m - 170 m
REAR RED	-	195 h	-
REAR RED FLASHING	-	300 h	-
DIMENSIONS	83 x 38 x 42 mm		
WEIGHT	183 g (without battery) / 283 g (with battery)		
THE SET INCLUDES	2 x Li-Ion battery, front helmet mount, rear helmet mount (battery & signal module), extension cord (1 m), USB-C cord, hard shell case		



IPX5 RATING

1,5 m IMPACT RESISTANCE

ADVANCED DIMMING SYSTEM

BATTERY LEVEL INDICATOR

DIFFUSER

USB-C CHARGING









Ultimo X1000 is a high-performance headlamp engineered for demanding industrial environments. It emits a maximum light output of 1000 lumens and provides a beam distance of up to 170 meters. The front white light features adjustable light intensity through an Advanced Dimming System, while the rear red light, which can be set to either steady or flashing modes, enhances user visibility and safety. This headlamp can operate for up to 148 hours, powered by two rechargeable 2600 mAh Li-ion batteries, charged via a USB-C port. The set includes front and rear helmet mounts, a 1-meter extension cord, a USB-C cord, and a hard shell carrying case. The Ultimo X1000 is impact-resistant from 1.5 meters and water-resistant to the IPX5 standard.

PRODUCT MEETS THE FOLLOWING STANDARDS: CE RoHS

MACTRONIC®

VALUE HIGHLIGHTS

5-YEAR WARRANTY

PATENTED DESIGN

ECO FRIENDLY PACKAGING

SCAN ME

Mactronic® Group Sp. z o. o., ul. Stargardzka 4, 54-156 Wrocław, Poland | +48 71 351 86 53 | export@mactronic.pl | www.mactronic.pl/en