Mactronic®

TRUSTED BY PROS®

TWIN BEAM

700 lm | 69 m

PWL0111

APPLICATIONS: AUTOMOTIVE SERVICES, DETAILING, WORK SAFETY, INDUSTRIAL, CONSTRUCTION, DIY, EDC

POWER SUPPLY	Li-Ion 3,7V 2600 mAh		
CHARGING TIME	4 h		
	LIGHT OUTPUT	**RUN TIME**	**BEAM DISTANCE**
FLOOD HIGH	700 lm	2 h 45 min	32 m
FLOOD MEDIUM	350 lm	4 h 30 min	-
FLOOD LOW	120 lm	12 h	-
SPOT	300 lm	4 h	69 m
DIMENSIONS	93,5 x 80 x 35,5 mm		
WEIGHT	210 g		
THE SET INCLUDES	USB-C cord		



- IPX5 RATING
- 2 m IMPACT RESISTANCE
- IK07 RATING
- USB-C
- MAGNET
- BATTERY LEVEL INDICATOR
- CRI 80
- ADJUSTABLE HEAD 180°







TWIN BEAM is a compact work light equipped with two independent light sources: a COB LED panel for wide-area illumination (FLOOD) and a focused LED (SPOT) with a beam distance of up to 69 meters. It operates in three lighting modes, allowing the user to adjust the output for various tasks. The adjustable magnetic base enables precise light direction. A battery level indicator on the back of the housing provides a quick status check. Powered by a 3.7V 2600 mAh Li-Ion battery, the light offers up to 12 hours of run time and charges via a USB-C port.TWIN BEAM functions effectively in temperatures from -10°C to +40°C and is resistant to impacts from drops of up to 2 meters. With a CRI of 80, it ensures accurate color rendering.

PRODUCT MEETS THE FOLLOWING STANDARDS: CE RoHS

MACTRONIC®
VALUE HIGHLIGHTS

- **5-YEAR WARRANTY**
- **PATENTED DESIGN**
- **ECO FRIENDLY PACKAGING**

SCAN ME

Mactronic® Group Sp. z o. o., ul. Stargardzka 4, 54-156 Wrocław, Poland | +48 71 351 86 53 | export@mactronic.pl | www.mactronic.pl/en