Mactronic®

TRUSTED BY PROS®

SKYLUX 200

20 000 lm | 315 m²

TL00010

APPLICATIONS: FIREFIGHTING, RESCUE, MILITARY, CONSTRUCTION, WORK SAFETY

LIGHT OUTPUT	20 000 lm
LIGHT RANGE	315 m²
LED LIGHTING POWER	200 W
OPERATING TEMPERATURE	-20°C - +60°C
HIGH ALTITUDE OPERATIONS	4500 m a.s.l.
POWER SUPPLY SYSTEM	
INPUT VOLTAGE	AC 230 V, 50 Hz
RATED POWER	350 W
LIGHTING DRONE	
DIMENSIONS (WITHOUT PADDLES)	185 × 185 × 85 mm
WEIGHT	< 250 g
WHEELBASE	230 mm
MAXIMUM FLIGHT ALTITUDE	12 m
CONTROL MODE	Hand-held Remote Controller
CONNECTION MODE	Wired Control
WIND RESISTANCE LEVEL	Class 6 (wind speed up to 50 km/h)
RAIN RESISTANCE LEVEL	Class 10
TETHERED BOX	
WEIGHT	< 10 kg (including drone and other accessories)
DIMENSIONS	About 500 × 380 × 240 mm
CORD LENGTH	About 12 m









POWER 200 W

WIND RESISTANCE: CLASS 6

RAIN RESISTANCE: CLASS 10

Skylux 200 is a ground-powered, tethered-drone lighting system. It ascends to 12 meters and provides 360° illumination up to 20,000 lumens. Ready to deploy in under five minutes, it requires no masts or UAV permits. Ideal for rescue missions, military operations, technical inspections, and construction sites. The power tether ensures continuous operation, while the wind- and rain-resistant design delivers reliable performance in demanding field conditions.

PRODUCT MEETS THE FOLLOWING STANDARDS: CE RoHS

MACTRONIC® VALUE HIGHLIGHTS

5-YEAR WARRANTY

PATENTED DESIGN

ECO FRIENDLY PACKAGING

SCAN ME

Mactronic® Group Sp. z o. o., ul. Stargardzka 4, 54-156 Wrocław, Poland | +48 71 351 86 53 | export@mactronic.pl | www.mactronic.pl/en